



# Power MOSFETS

## DATASHEET

---

**LM40046NAP3A**

N-Channel  
Enhancement Mode MOSFET

 Leadpower-semi CO., LTD.

 [sales@leadpower-semi.com](mailto:sales@leadpower-semi.com)

 (03) 6577339 FAX : (03) 6577229

 [www.leadpower-semi.com](http://www.leadpower-semi.com)




Quality Management Systems

ISO 9001:2015 Certificate

## N-Channel Enhancement Mode MOSFET

### Pin Description



### Product Summary

Symbol	N-Channel	Unit
$V_{DSS}$	40	V
$R_{DS(ON)-Max}$	5	m $\Omega$
ID	93	A

### Feature

- Fast switching speed
- Reliable and Rugged
- ROHS Compliant & Halogen-Free
- 100% UIS Tested
- 100% RG Tested

### Applications

- Portable Equipment
- Battery Powered System

### Ordering Information

Orderable Part Number	Package Type	Form	Shipping
LM40046NAP3A	TO220-3L	Tube	50 / Tube

### Absolute Maximum Ratings (T<sub>J</sub>=25°C Unless Otherwise Noted)

Symbol	Parameter	N-Channel	Unit	
$V_{DSS}$	Drain-Source Voltage	40	V	
$V_{GSS}$	Gate-Source Voltage	±20		
$T_J$	Maximum Junction Temperature	150	°C	
$T_{STG}$	Storage Temperature Range	-55 to 150	°C	
$I_{DM}^{①}$	Pulse Drain Current Tested	T <sub>c</sub> =25°C	184	A
$I_D$	Continuous Drain Current	T <sub>c</sub> =25°C	93	A
		T <sub>c</sub> =100°C	59	
$P_D$	Maximum Power Dissipation	T <sub>c</sub> =25°C	83	W
		T <sub>c</sub> =100°C	33	
$I_{AS}^{②}$	Avalanche Current, Single pulse	L=0.1mH	35	A
$E_{AS}^{②}$	Avalanche Energy, Single pulse	L=0.1mH	61	mJ

### Thermal Characteristics

Symbol	Parameter	Rating	Unit	
$R_{\theta JC}$	Thermal Resistance-Junction to Case	Steady State	1.5	°C/W
$R_{\theta JA}^{③}$	Thermal Resistance-Junction to Ambient	Steady State	62.5	°C/W

Note ① : Max. current is limited by bonding wire

Note ② : UIS tested and pulse width are limited by maximum junction temperature 150°C

Note ③ : Surface Mounted on 1in<sup>2</sup> FR-4 board with 1oz.







## N-Channel Electrical Characteristics (T<sub>J</sub>=25°C Unless Otherwise Noted)


Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
<b>Static Electrical Characteristics</b>						
<b>BV<sub>DSS</sub></b>	Drain-Source Breakdown Voltage	V <sub>GS</sub> =0V, I <sub>DS</sub> =250uA	40	-	-	V
<b>I<sub>DSS</sub></b>	Zero Gate Voltage Drain Current	V <sub>DS</sub> =32V, V <sub>GS</sub> =0V	-	-	1	uA
<b>V<sub>GS(th)</sub></b>	Gate Threshold Voltage	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>DS</sub> =250uA	1.3	1.7	2.2	V
<b>I<sub>GSS</sub></b>	Gate Leakage Current	V <sub>GS</sub> =±20V, V <sub>DS</sub> =0V	-	-	±100	nA
<b>R<sub>DS(ON)</sub><sup>④</sup></b>	Drain-Source On-state Resistance	V <sub>GS</sub> =10V, I <sub>DS</sub> =20A	-	4.2	5	mΩ
		V <sub>GS</sub> =4.5V, I <sub>DS</sub> =15A	-	4.9	6.4	
<b>g<sub>fs</sub></b>	Forward Transconductance	V <sub>DS</sub> =5V, I <sub>DS</sub> =20A	-	2.7	-	S
<b>Dynamic Characteristics<sup>®</sup></b>						
<b>R<sub>G</sub></b>	Gate Resistance	V <sub>GS</sub> =0V, V <sub>DS</sub> =0V, Freq.=1MHz	-	3	-	Ω
<b>C<sub>iss</sub></b>	Input Capacitance	V <sub>GS</sub> =0V, V <sub>DS</sub> =20V, Freq.=1MHz	-	3105	-	pF
<b>C<sub>oss</sub></b>	Output Capacitance					
<b>C<sub>rss</sub></b>	Reverse Transfer Capacitance					
<b>t<sub>d(ON)</sub></b>	Turn-on Delay Time	V <sub>GS</sub> =10V, V <sub>DS</sub> =20V, I <sub>D</sub> =1A, R <sub>GEN</sub> =6Ω	-	15.2	-	nS
<b>t<sub>r</sub></b>	Turn-on Rise Time					
<b>t<sub>d(OFF)</sub></b>	Turn-off Delay Time					
<b>t<sub>f</sub></b>	Turn-off Fall Time					
<b>Q<sub>g</sub></b>	Total Gate Charge	V <sub>GS</sub> =4.5V, V <sub>DS</sub> =25V, I <sub>D</sub> =20A	-	34	-	nC
<b>Q<sub>g</sub></b>	Total Gate Charge	V <sub>GS</sub> =10V, V <sub>DS</sub> =25V, I <sub>D</sub> =20A	-	68	-	
<b>Q<sub>gs</sub></b>	Gate-Source Charge		-	9	-	
<b>Q<sub>gd</sub></b>	Gate-Drain Charge		-	11.5	-	
<b>Source-Drain Characteristics</b>						
<b>V<sub>SD</sub><sup>④</sup></b>	Diode Forward Voltage	I <sub>SD</sub> =15A, V <sub>GS</sub> =0V	-	0.8	1.1	V
<b>t<sub>rr</sub></b>	Reverse Recovery Time	I <sub>F</sub> =15A, V <sub>R</sub> =20V	-	27.2	-	nS
<b>Q<sub>rr</sub></b>	Reverse Recovery Charge	dI <sub>F</sub> /dt=100A/μs	-	20.4	-	nC

Note ④ : Pulse test (pulse width≤300us, duty cycle≤2%).


Note ⑤ : Guaranteed by design, not subject to production testing.

## N-Channel Typical Characteristics







$V_{DS}$  - Drain - Source Voltage (V)  
Figure 7. Capacitance




$Q_g$ , Total Gate Charge (nC)  
Figure 8. Gate Charge Characteristics




$T_j$  - Junction Temperature (°C)  
Figure 9. Power Dissipation



$T_j$  - Junction Temperature (°C)  
Figure 10. Drain Current



$V_{DS}$  - Drain-Source Voltage (V)  
Figure 11. Safe Operating Area



$t_1$ , Square Wave Pulse Duration(s)  
Figure 12.  $R_{\theta JC}$  Transient Thermal Impedance